

**Information requirements
(air-to-air air conditioners)**

Model(s):GUD125PHS/A-T、GUD125W/NhA-X							
Outdoor side heat exchanger of air conditioner	air						
Indoor side heat exchanger of air conditioner	air						
Type	compressor driven vapour compression						
If applicable: driver of compressor	electric motor						
Item	Symbol	Value	Unit	Item	Symbol	Value	Unit
Rated cooling capacity	$P_{rated,c}$	12.1	kW	Seasonal space cooling energy efficiency	$\eta_{s,c}$	244.4	%
Declared cooling capacity for part load at given outdoor temperatures T_j and indoor 27°/19 °C (dry/wet bulb)				Declared energy efficiency ratio or gas utilisation efficiency/auxiliary energy factor for part load at given outdoor temperatures T_j			
$T_j = + 35\text{ °C}$	P_{dc}	12.21	kW	$T_j = + 35\text{ °C}$	EER_d	3.26	—
$T_j = + 30\text{ °C}$	P_{dc}	8.66	kW	$T_j = + 30\text{ °C}$	EER_d	4.51	—
$T_j = + 25\text{ °C}$	P_{dc}	5.56	kW	$T_j = + 25\text{ °C}$	EER_d	7.14	—
$T_j = + 20\text{ °C}$	P_{dc}	3.77	kW	$T_j = + 20\text{ °C}$	EER_d	10.65	—
Degradation co-efficient for air conditioners(*)	C_{dc}	0.25	—				—
Power consumption in modes other than 'active mode'							
Off mode	P_{OFF}	0.00357	kW	Crankcase heater mode	P_{CK}	0.0000	kW
Thermostat-off mode	P_{TO}	0.01497	kW	Standby mode	P_{SB}	0.00357	kW
Other items							
Capacity control	variable			For air-to-air air conditioner: air flow rate, outdoor measured	—	5900	m^3/h
Sound power level, indoor/outdoor measured	L_{WA}	66.4/69.2	dB				
If engine driven: Emissions of nitrogen oxides	$NO_x(**)$	/	mg/kWh fuel input GCV				
GWP of the refrigerant	675		kg CO ₂ eq (100 years)				
Contact details: +420 532 197 950, info@greeczech.cz				Name of manufacturer: GREE Czech & Slovak s.r.o. Košuličova 778/39, Brno, 619 00, Czech Republic			
(*) If C_{dc} is not determined by measurement then the default degradation coefficient air conditioners shall be 0.25. (**) From 26 September 2018. Where information relates to multi-split air conditioners, the test result and performance data may be obtained on the basis of the performance of the outdoor unit, with a combination of indoor unit(s) recommended by the manufacturer or importer.							

**Information requirements
(heat pump)**

Model(s):GUD125PHS/A-T、GUD125W/NhA-X							
Outdoor side heat exchanger of heat pump	air						
Indoor side heat exchanger of heat pump	air						
Indication if the heater is equipped with a supplementary heater	no						
If applicable: driver of compressor	electric motor						
Parameters declared for	Average climate condition						
Item	symbol	value	unit	Item	symbol	value	unit
Rated heating capacity	$P_{rated,h}$	13.5	kW	Seasonal space heating energy efficiency	$\eta_{s,h}$	159.0	%
Declared heating capacity for part load at indoor temperature 20 °C and outdoor temperature T_j				Declared coefficient of performance or gas utilisation efficiency/auxiliary energy factor for part load at given outdoor temperatures T_j			
$T_j = -7\text{ °C}$	P_{dh}	8.91	kW	$T_j = -7\text{ °C}$	COP_d	2.56	—
$T_j = +2\text{ °C}$	P_{dh}	5.54	kW	$T_j = +2\text{ °C}$	COP_d	4.05	—
$T_j = +7\text{ °C}$	P_{dh}	3.53	kW	$T_j = +7\text{ °C}$	COP_d	5.35	—
$T_j = +12\text{ °C}$	P_{dh}	3.04	kW	$T_j = +12\text{ °C}$	COP_d	5.85	—
T_{biv} = bivalent temperature	P_{dh}	8.91	kW	T_{biv} = bivalent temperature	COP_d	2.56	—
T_{OL} = operation limit	P_{dh}	7.91	kW	T_{OL} = operation limit	COP_d	2.45	—
For air-to-water heat pumps: $T_j = -15\text{ °C}$ (if $TOL < -20\text{ °C}$)	P_{dh}	NA	kW	For water-to-air heat pumps: $T_j = -15\text{ °C}$ (if $TOL < -20\text{ °C}$)	COP_d	NA	—
Bivalent temperature	T_{biv}	-7.00	°C	For water-to-air heat pumps: Operation limit temperature	T_{ol}	-10.00	°C
Degradation co-efficient heat pumps(**)	C_{dh}	0.25	—				
Power consumption in modes other than 'active mode'				Supplementary heater			
Off mode	P_{OFF}	0.00357	kW	Back-up heating capacity (*)	el_{bu}	—	kW
Thermostat-off mode	P_{TO}	0.01517	kW	Type of energy input			
Crankcase heater mode	P_{CK}	0.0000	kW	Standby mode	P_{SB}	0.00357	kW
Other items							
Capacity control	variable			For air-to-air heat pumps: air flow rate, outdoor measured	—	5900	m^3/h
Sound power level, indoor/outdoor measured	L_{WA}	66.1/69.5	dB				
Emissions of nitrogen oxides (if applicable)	$NO_x(**)$	/	mg/kWh input GCV	For water/brine-to-air heat pumps: Rated brine or water flow rate, outdoor side heat exchanger	—	—	m^3/h
GWP of the refrigerant	675		kg CO ₂ eq (100 years)				
Contact details: +420 532 197 950, info@greeczech.cz				Name of manufacturer: GREE Czech & Slovak s.r.o., Košuličova 778/39, Brno, 619 00, Czech Rep.			
(*)							
(**) If C_{dh} is not determined by measurement then the default degradation coefficient of heat pumps shall be 0.25.(***) From 26 September 2018.							
Where information relates to multi-split heat pumps, the test result and performance data may be obtained on the basis of the performance of the outdoor unit, with a combination of indoor unit(s) recommended by the manufacturer or importer.							

**Information requirements
(air-to-air air conditioners)**

Model(s):GUD125T/A-T、GUD125W/NhA-X							
Outdoor side heat exchanger of air conditioner	air						
Indoor side heat exchanger of air conditioner	air						
Type	compressor driven vapour compression						
If applicable: driver of compressor	electric motor						
Item	Symbol	Value	Unit	Item	Symbol	Value	Unit
Rated cooling capacity	$P_{rated,c}$	12.1	kW	Seasonal space cooling energy efficiency	$\eta_{s,c}$	243.5	%
Declared cooling capacity for part load at given outdoor temperatures T_j and indoor 27°/19 °C (dry/wet bulb)				Declared energy efficiency ratio or gas utilisation efficiency/auxiliary energy factor for part load at given outdoor temperatures T_j			
$T_j = + 35 \text{ °C}$	P_{dc}	12.42	kW	$T_j = + 35 \text{ °C}$	EER_d	3.12	—
$T_j = + 30 \text{ °C}$	P_{dc}	8.88	kW	$T_j = + 30 \text{ °C}$	EER_d	4.56	—
$T_j = + 25 \text{ °C}$	P_{dc}	5.56	kW	$T_j = + 25 \text{ °C}$	EER_d	7.18	—
$T_j = + 20 \text{ °C}$	P_{dc}	4.44	kW	$T_j = + 20 \text{ °C}$	EER_d	10.75	—
Degradation co-efficient for air conditioners(*)	C_{dc}	0.25	—				—
Power consumption in modes other than ‘active mode’							
Off mode	P_{OFF}	0.00341	kW	Crankcase heater mode	P_{CK}	0.0000	kW
Thermostat-off mode	P_{TO}	0.01473	kW	Standby mode	P_{SB}	0.00341	kW
Other items							
Capacity control	variable			For air-to-air air conditioner: air flow rate, outdoor measured	—	5900	m^3/h
Sound power level, indoor/outdoor measured	L_{WA}	60.6/69.2	dB				
If engine driven: Emissions of nitrogen oxides	$NO_x(***)$	/	mg/kWh fuel input GCV				
GWP of the refrigerant	675		kg CO ₂ eq (100 years)				
Contact details: +420 532 197 950, info@greeczech.cz				Name of manufacturer: GREE Czech & Slovak s.r.o., Košuličova 778/39, Brno, 619 00, Czech Republic			
(*) If C_{dc} is not determined by measurement then the default degradation coefficient air conditioners shall be 0.25. (**) From 26 September 2018. Where information relates to multi-split air conditioners, the test result and performance data may be obtained on the basis of the performance of the outdoor unit, with a combination of indoor unit(s) recommended by the manufacturer or importer.							

**Information requirements
(heat pump)**

Model(s):GUD125T/A-T、GUD125W/NhA-X							
Outdoor side heat exchanger of heat pump	air						
Indoor side heat exchanger of heat pump	air						
Indication if the heater is equipped with a supplementary heater	no						
If applicable: driver of compressor	electric motor						
Parameters declared for	Average climate condition						
Item	symbol	value	unit	Item	symbol	value	unit
Rated heating capacity	$P_{rated,h}$	13.5	kW	Seasonal space heating energy efficiency	$\eta_{s,h}$	158.6	%
Declared heating capacity for part load at indoor temperature 20 °C and outdoor temperature T_j				Declared coefficient of performance or gas utilisation efficiency/auxiliary energy factor for part load at given outdoor temperatures T_j			
$T_j = -7\text{ °C}$	P_{dh}	8.92	kW	$T_j = -7\text{ °C}$	COP_d	2.51	—
$T_j = +2\text{ °C}$	P_{dh}	5.45	kW	$T_j = +2\text{ °C}$	COP_d	3.97	—
$T_j = +7\text{ °C}$	P_{dh}	3.53	kW	$T_j = +7\text{ °C}$	COP_d	5.45	—
$T_j = +12\text{ °C}$	P_{dh}	2.98	kW	$T_j = +12\text{ °C}$	COP_d	6.22	—
T_{biv} = bivalent temperature	P_{dh}	8.83	kW	T_{biv} = bivalent temperature	COP_d	2.51	—
T_{OL} = operation limit	P_{dh}	8.76	kW	T_{OL} = operation limit	COP_d	2.44	—
For air-to-water heat pumps: $T_j = -15\text{ °C}$ (if $TOL < -20\text{ °C}$)	P_{dh}	NA	kW	For water-to-air heat pumps: $T_j = -15\text{ °C}$ (if $TOL < -20\text{ °C}$)	COP_d	NA	—
Bivalent temperature	T_{biv}	-7.00	°C	For water-to-air heat pumps: Operation limit temperature	T_{ol}	-10.00	°C
Degradation co-efficient heat pumps(**)	C_{dh}	0.25	—				
Power consumption in modes other than 'active mode'				Supplementary heater			
Off mode	P_{OFF}	0.00341	kW	Back-up heating capacity (*)	el_{bu}	—	kW
Thermostat-off mode	P_{TO}	0.02334	kW	Type of energy input			
Crankcase heater mode	P_{CK}	0.0000	kW	Standby mode	P_{SB}	0.00341	kW
Other items							
Capacity control	variable			For air-to-air heat pumps: air flow rate, outdoor measured	—	5900	m^3/h
Sound power level, indoor/outdoor measured	L_{WA}	59.6/69.5	dB				
Emissions of nitrogen oxides (if applicable)	$NO_x(***)$	/	mg/kWh input GCV	For water/brine-to-air heat pumps: Rated brine or water flow rate, outdoor side heat exchanger	—	—	m^3/h
GWP of the refrigerant	675		kg CO ₂ eq (100 years)				
Contact details: +420 532 197 950, info@greeczech.cz				Name of manufacturer: GREE Czech & Slovak s.r.o., Košuličova 778/39, Brno, 619 00, Czech Rep.			

(*)

(**) If C_{dh} is not determined by measurement then the default degradation coefficient of heat pumps shall be 0.25.(***)
From 26 September 2018.

Where information relates to multi-split heat pumps, the test result and performance data may be obtained on the basis of the performance of the outdoor unit, with a combination of indoor unit(s) recommended by the manufacturer or importer.

**Information requirements
(air-to-air air conditioners)**

Model(s):GUD125ZD/A-T、GUD125W/NhA-X							
Outdoor side heat exchanger of air conditioner	air						
Indoor side heat exchanger of air conditioner	air						
Type	compressor driven vapour compression						
If applicable: driver of compressor	electric motor						
Item	Symbol	Value	Unit	Item	Symbol	Value	Unit
Rated cooling capacity	$P_{rated,c}$	12.1	kW	Seasonal space cooling energy efficiency	$\eta_{s,c}$	243.7	%
Declared cooling capacity for part load at given outdoor temperatures T_j and indoor 27°/19 °C (dry/wet bulb)				Declared energy efficiency ratio or gas utilisation efficiency/auxiliary energy factor for part load at given outdoor temperatures T_j			
$T_j = + 35 \text{ °C}$	P_{dc}	12.23	kW	$T_j = + 35 \text{ °C}$	EER_d	3.21	—
$T_j = + 30 \text{ °C}$	P_{dc}	8.69	kW	$T_j = + 30 \text{ °C}$	EER_d	5.05	—
$T_j = + 25 \text{ °C}$	P_{dc}	5.64	kW	$T_j = + 25 \text{ °C}$	EER_d	6.57	—
$T_j = + 20 \text{ °C}$	P_{dc}	3.82	kW	$T_j = + 20 \text{ °C}$	EER_d	10.52	—
Degradation co-efficient for air conditioners(*)	C_{dc}	0.25	—				—
Power consumption in modes other than ‘active mode’							
Off mode	P_{OFF}	0.00341	kW	Crankcase heater mode	P_{CK}	0.0000	kW
Thermostat-off mode	P_{TO}	0.01473	kW	Standby mode	P_{SB}	0.00341	kW
Other items							
Capacity control	variable			For air-to-air air conditioner: air flow rate, outdoor measured	—	5900	m^3/h
Sound power level, indoor/outdoor measured	L_{WA}	61.2/69.2	dB				
If engine driven: Emissions of nitrogen oxides	$NO_x(**)$	/	mg/kWh fuel input GCV				
GWP of the refrigerant	675		kg CO ₂ eq (100 years)				
Contact details: +420 532 197 950, info@greeczech.cz				Name of manufacturer: GREE Czech & Slovak s.r.o., Košuličova 778/39, Brno, 619 00, Czech Republic			
(*) If C_{dc} is not determined by measurement then the default degradation coefficient air conditioners shall be 0.25. (**) From 26 September 2018. Where information relates to multi-split air conditioners, the test result and performance data may be obtained on the basis of the performance of the outdoor unit, with a combination of indoor unit(s) recommended by the manufacturer or importer.							

**Information requirements
(heat pump)**

Model(s):GUD125ZD/A-T、GUD125W/NhA-X							
Outdoor side heat exchanger of heat pump	air						
Indoor side heat exchanger of heat pump	air						
Indication if the heater is equipped with a supplementary heater	no						
If applicable: driver of compressor	electric motor						
Parameters declared for	Average climate condition						
Item	symbol	value	unit	Item	symbol	value	unit
Rated heating capacity	$P_{rated,h}$	13.5	kW	Seasonal space heating energy efficiency	$\eta_{s,h}$	157.2	%
Declared heating capacity for part load at indoor temperature 20 °C and outdoor temperature T_j				Declared coefficient of performance or gas utilisation efficiency/auxiliary energy factor for part load at given outdoor temperatures T_j			
$T_j = -7\text{ °C}$	P_{dh}	9.04	kW	$T_j = -7\text{ °C}$	COP_d	2.39	—
$T_j = +2\text{ °C}$	P_{dh}	5.41	kW	$T_j = +2\text{ °C}$	COP_d	3.85	—
$T_j = +7\text{ °C}$	P_{dh}	3.55	kW	$T_j = +7\text{ °C}$	COP_d	5.56	—
$T_j = +12\text{ °C}$	P_{dh}	3.04	kW	$T_j = +12\text{ °C}$	COP_d	6.85	—
T_{biv} = bivalent temperature	P_{dh}	9.04	kW	T_{biv} = bivalent temperature	COP_d	2.39	—
T_{OL} = operation limit	P_{dh}	8.25	kW	T_{OL} = operation limit	COP_d	3.35	—
For air-to-water heat pumps: $T_j = -15\text{ °C}$ (if $TOL < -20\text{ °C}$)	P_{dh}	NA	kW	For water-to-air heat pumps: $T_j = -15\text{ °C}$ (if $TOL < -20\text{ °C}$)	COP_d	NA	—
Bivalent temperature	T_{biv}	-7.00	°C	For water-to-air heat pumps: Operation limit temperature	T_{ol}	-10.00	°C
Degradation co-efficient heat pumps(**)	C_{dh}	0.25	—				
Power consumption in modes other than 'active mode'				Supplementary heater			
Off mode	P_{OFF}	0.00341	kW	Back-up heating capacity (*)	el_{bu}	—	kW
Thermostat-off mode	P_{TO}	0.02334	kW	Type of energy input			
Crankcase heater mode	P_{CK}	0.0000	kW	Standby mode	P_{SB}	0.00341	kW
Other items							
Capacity control	variable			For air-to-air heat pumps: air flow rate, outdoor measured	—	5900	m^3/h
Sound power level, indoor/outdoor measured	L_{WA}	60.9/69.5	dB				
Emissions of nitrogen oxides (if applicable)	NO_x (**)	/	mg/kWh input GCV	For water/brine-to-air heat pumps: Rated brine or water flow rate, outdoor side heat exchanger	—	—	m^3/h
GWP of the refrigerant	675		kg CO ₂ eq (100 years)				
Contact details: +420 532 197 950, info@greeczech.cz				Name of manufacturer: GREE Czech & Slovak s.r.o., Košuličova 778/39, Brno, 619 00, Czech Rep.			
(*)							
(**) If C_{dh} is not determined by measurement then the default degradation coefficient of heat pumps shall be 0.25.(***) From 26 September 2018.							
Where information relates to multi-split heat pumps, the test result and performance data may be obtained on the basis of the performance of the outdoor unit, with a combination of indoor unit(s) recommended by the manufacturer or importer.							